

# DISSIPATIVE TABLE MAT

Double layer table mat with excellent grounding properties, soldering heat resistant, available in different colours and in complete rolls or pre-cut.



## PHYSICAL PROPERTIES

|                      |   |
|----------------------|---|
| Abrasion resistance  | < 200 mm <sup>3</sup><br>(ISO 4649 procedure A) |
| Hardness             | 75 Shore A (ISO 7619)                           |
| Residual indentation | < 0.2 mm (EN 433)                               |
| Colour reflexion     | Grey: 19%<br>Blue: 29%                          |
| Thickness            | 2.0 mm  |
| Surface              | Rugged  |

## ELECTRICAL PROPERTIES

|                              |   |
|------------------------------|---|
| Resistant to ground Rg       | Per EN 61340-2-3:<br>typical 10 <sup>7</sup> Ω  |
| Point to point resistance Rp | Per EN 61340-2-3:<br>typical <10 <sup>8</sup> Ω |
| Compliant to                 | EN 61340-5-1                                    |

## FEATURES & PART-NUMBERS

| SHAPE         | DIMENSION      | COLOUR | PARTNUMBER  |
|---------------|----------------|--------|-------------|
| Complete Roll | 1.22 m x 10 m  | Grey   | Q1TD0143006 |
|               | 1.22 m x 10 m  | Blue   | Q1TD0113004 |
| Pre-cut       | 60 cm x 90 cm  | Grey   | Q1TD0140002 |
|               | 60 cm x 90 cm  | Blue   | Q1TD0110002 |
|               | 60 cm x 120 cm | Grey   | Q1TD0140003 |
|               | 60 cm x 120 cm | Blue   | Q1TD0110003 |

## OPTIONS

Other cut sizes, other mat equipments are available.